

1

2

3

RUBBER PART GENERAL TOLERANCE				
PART DIM.	1	2	③	
0 TO 3	± 0.2	± 0.3	± 0.4	
3 TO 6	± 0.2	± 0.4	± 0.5	
6 TO 10	± 0.3	± 0.5	± 0.6	
10 TO 18	± 0.3	± 0.6	± 0.8	
18 TO 30	± 0.4	± 0.8	± 1.0	
30 TO 50	± 0.5	± 1.0	± 1.5	
50 TO 80	± 0.6	± 1.2	± 2.0	
80 TO 120	± 0.7	± 1.4	± 2.5	
120 TO 180	± 0.8	± 1.6	± 3.0	
180 TO 250	± 1.0	± 2.0	± 4.0	
250 TO 315	± 1.2	± 2.5	± 5.0	
315 TO 400	± 1.5	± 3.0	± 6.0	
400 TO 500	± 1.8	± 3.5	± 7.0	
500 OVER	± 0.4%	± 0.8%	± 1.5%	

注記

1. 色: 濃灰色トスル.

2. 材料: 含油NBR

NOTES

1. COLOR : DARK GRAY

2. MATL&SPEC : SELF-LUBRICATING. NBR

A

SEC. A-A

ISSUE MARK

								CUSTOMER				MATL. SPEC.				TREAT. & FIN.			
								CUSTOMER PART NO.				CUSTOMER DWG NO.				SEE NOTES			
																NAME			
90.10.01		NEW		C90-M079		T. S		OFFICE				STD LIB NO.				187 PLUGGING RUBBER			
LET	DATE	REVISION RECORD				NO.	CHKD	VENDOR				-----				STOPPER			
GENERAL TOLERANCE								VENDOR NO.				-----							
	10MAX	50MAX	100MAX	250MAX	250QVR	ANGLE	ECCENT	DWG TYPE	DWG SOURCE	DWG DATE	UNIT	SCL	ANGLE	PART NO.					
A	±0.15	±0.2	±0.3	±0.5	±0.75	±30'	0.1	R	NEW	90.10.01	mm	10/1	3	7157-8763					
B	±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	APPROVED	CHECKED	CHECKED	DESIGN	DRAWN	DWG NO.		7157-8763:R				
C	±0.3	±0.5	±0.8	±1.4	±2	±30'	0.15				M. TSUJI	T. MAKITA	TRIAL PART NO.						
SPECIFIED								WEIGHT											
RUBBER PART GENERAL TOLERANCE 3								g				90.11.02 90.11.02 90.10.31 88.08.20 90.10.01				YAZAKI CORPORATION			

1

2

3

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Yazaki:](#)

[71578763](#)